

# DOUBLE BAG

## KIDNEY/ BYPASS FILTRATION SYSTEM

REMOVAL OF CONTAMINATION OR COMBINATION OF  
WATER AND CONTAMINANTS

The Perfect Filtration Double Bag was designed for large and Coarse applications where pre filtration and oil turnaround tie are required. Small and compact for easy installation. Extremely effective for continues Filtration applications.



## PERFECT FILTRATION

### HYDRAULIC SYSTEMS

Ideal for power packs, tanks, and more.

### GEARBOXES

Keeps your machinery running smoothly by removing contaminants.

### LUBRICATION SYSTEMS

Ensures the purity of oils and lubricants

### GLYCOL APPLICATIONS

Effective in systems using glycol fluids.

## SPECIFICATION

- **AC Input Voltage:** 220V / 320V / 525V
- **Electric Motor Size:** 2.2Kw – 3.5Kw
- **Pump Size:** 22CC – 46CC Gear Pump
- **Flow Rate:** 30.8L/min – 64.4L/min
- **Maximum Temperature:** 60°C
- **Bag Housing Options:** Standard or with Magnetic Filtration
- **Bag Filter Range:** 0.5 Micron – 200 Micron Nominal

## BUILT FOR SAFETY AND DURABILITY

Safety and longevity are paramount:

- **Frame:** powder-coated for corrosion protection.
- **Safety Features:** Includes an emergency stop, electronic pressure control, and mechanical pressure control.
- **Connection Points:** Fixed or mobile connections to suit various installations.
- **Pressure Control:** Internal pressure relief valve ensures safe operation.

Make the smart choice for your industrial filtration challenges and choose the Double Bag

Contact Us Today:

072 717 0572 /sales@perfectfiltration.co.za